## A Highly Adaptable Ass

## AC500 [500kg x 10.5m]

The compact pick and carry AC500 Assembly Crane is the ideal machine for lifting in restricted access areas.

This industrial assembly lifting crane allows operators to pick and carry loads of up to 500kg and can boom out to an impressive 5.1 metres. The AC500 is able to lift to a height of 10.5 metres and its 355° slew rotation and onboard electric battery make it the optimum machine for both lifting and travelling with loads.

This compact crane benefits from a small working footprint thanks to its compact width, measuring at less than one metre (0.98m). The cranes low marking tyres make it the perfect machine for internal lifting projects for processing plants, manufacturing industries and sensitive environments.

## **Key Features**

- Maximum safe working load 500kg x 10.5m
- Max working radius 5.1m
- 355° slew rotation with stopping point
- Steering lock 85°
- Angle of Inclination 1.5° with Load
- Weight of crane: 4800kg
- Turning radius: 1.47 m outside/ 1.20 m inside
- Solid rubber low marking wheels
- Battery powered: 24 V 330Ah / 230V charger / 16A 110v charger







## **Technical Specifications**

| Safe working load    | capacity:             | 500kg   |
|----------------------|-----------------------|---|
| Weight               | weight:               | 4800kg  |
| Width                | width:                | 980mm   |
| Length               | length:               | 2980mm  |
| Height               | height:               | 2370mm  |
| Slew rotation        | rotation:             | 355° with stopping point                          |
| Steering lock        | lock:                 | 85°   |
| Max working height   | tilt:                 | 9.4m  |
| Max working radius   | radius:               | 5.1m  |
| Turning radius       | radius:               | 1.47m outside / 1.2m inside                       |
| Wheels               | wheels:               | solid rubber low marking                          |
| Max. gradeability    | grade:                | 9°  |
| Max. ground pressure | pressure              | 2800kg/wheel                                      |
| Pad head slew        | powered slew:         | 90° left & right                                  |
| Power requirements   | rechargeable battery: | 24 V 330 Ah with 230v charger<br>16A 110v charger |









