

Access Platforms

14m Electric & Hydraulic

SWSL14 DC/HD Scissor Lifts [14m]

The Sunward SWSL1412 DC and HD Scissor Lifts have been specially designed for helping operators to install glazing, signage, cladding, steelwork, timber frames and more. Operators can work safely and efficiently at heights of up to 14m with these mini yet mighty scissor lifts.

With a platform height of 12m and an overall height of 14m these MEWPs are the perfect lifting solution for a variety of different projects. Boasting a lifting capacity of up to 320kg and a maximum occupancy of 2 people, these Scissor Lifts will be ideal to grow your fleet, alternatively they are available to hire from GGR Group.

These compact scissor lifts are only 1170mm wide and have a stowed height of 2630mm which means that they are small enough to fit into some of the most confined spaces such as shopping centres, sports halls and hospitals, but are also perfect to work in warehouses, storage facilities and more. With a small turning radius of 2200mm and dual front wheel drive, these nimble MEWPs are ideal to have in any small spaces or size-sensitive projects.

Complete with standard non marking wheels, these versatile scissor lifts can work on internal light-coloured and polished surfaces and external flat ground.

Reference Code

Hydraulic Drive: **SWSL14HD**

Electric Drive: **SWSL14DC**



Technical Specifications

Max platform height	12m
Max working height	14m
Platform length	2270mm
Platform width	1150mm
Capacity	320kg
Extension capacity	113kg
Drive speed (DC)	0.8km/h (elevated), 4.0km/h (stowed)
Drive speed (HD)	0.8km/h (elevated), 3.2km/h (stowed)
Turning radius	0mm (inside), 2200mm (outside)
Raise/lower speed	62s / 42s
Gradeability	25%
Max working angle	1.5° (lateral), 3° (longitudinal)
Battery	4x12V/300Ah
Charger	24V/30Ah
Weight	3000kg (electric), 2980kg (hydraulic)
Hydraulic tank capacity	20L (HD model only)

The non marking tyres allow the SWSL14 Scissor Lifts to be used in sites with sensitive flooring



A moveable joystick allows the operator free control to move, rise and lower the MEWPs either on or at the base of the platform



Easy diagnostics are possible thanks to the in-built USB port where a smartphone can be used to problem solve



The long-life batteries ensure a long run-time between charging as well as having zero emissions and a low noise output

Foldable rails means the compact SWSL14 Scissor Lifts reduce their stowed height even further from 2630mm to 2090mm

Our high reaching SWSL14's maximum platform height of 12m gives users an overall working height of 14m



Key Features

- Capacity: 320kg (main platform), 113kg (extending platform)
- Dimensions: 2470mm (l) x 1170mm (w) x 2630mm (h)
- Turning radius: 2200mm (outside), 0mm (inside)
- Maximum occupancy: 2 people
- Hydraulic or electric DC motor driven
- Non marking tyres
- Tilt sensor with alarm
- Pothole protection
- Dual front wheel drive
- Weight: 3000kg (hydraulic), 2980kg (electric)



The SWSL14 comes fitted with a self-locking gate for operator safety



Lifting eyes are included for ease of transport or moving from level to level by crane.

Technical Data (approx. mm)

